

A 365922

Certified, Filed and or Recorded on  
May 19, 2009 AT 11:21AM


Signed: *M*  
MARILYN J NOVAK  
BENTON COUNTY MINNESOTA  
MARILYN J NOVAK  
COUNTY RECORDER

### CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 9, Township 37 North, Range 29 West, Fourth Principal Meridian, Benton County, Minnesota.

At this corner location shown on the sketch:

- On 5/11/2009 found a 6-inch by 6-inch square granite stone with center hole.  
Note: Monument was temporarily removed looking for additional evidence under stone.
- left monument as found     lowered monument     removed monument (explain)
- On 5/12/2009 placed an 1/2" x 14" Pipe, capped 19552



Statement of evidence for this corner location is on back of this page.

I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a Licensed Land Surveyor under the laws of the State of Minnesota.

Signature *Jerome C. Wittstock*  
Benton County Surveyor  
License No. 19552

Date: 19 MAY 2009

Benton County Surveyor's Office  
 Jerome C. Wittstock, County Surveyor  
 Minnesota License No. 19552

**Statement of Evidence:****H093**

The East Quarter Corner of Section 9, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

12" Sugar	S 21 ½ W	18 links
18" Sugar	N 72 E	32 links

1933 County Engineer's Notebook No. 72 contains survey of County road running west to east. Notes show corner marked by a granite monument in center of road intersection. Ties:

F.P.	NW	47.4'
T.P.	SE	73.1'

1937 County Engineer's Notebook No. 99 contains a road survey for CAR No. 28 running south to north. Notes show corner marked by a granite monument in center of SAR No. 13 with same ties as below. Stationing gives distances of 2627.5 feet to the SE corner and 2626.2 feet to the NE corner with a delta angle of 0-03' right.

1959 County Engineer's Notebook No. 209 contains a road survey for CSAH No. 13 running west to east. Corner is shown as a granite monument in the 4-way road intersection. 1961 ties are the same as below.

County Surveyor's Record Book 1, page 477, shows the following:

1937 - Granite Monument

FP	NW	47.4
TP	SE	73.1

1959 Ties by Kotsmith

PP	SW	53.85
FP	NW	56.0
TP	NE	49.4

1961 County Highway ties to granite mon.

PP	SW	53.5
FP	NW	64.2
TP	NE	49.4

1997 William Lunser, LS 9394, gives a distance of 2655.06 feet to the NE corner of Section 9 on Certificate for NE corner of Sec. 9 (Doc. No. 283108).

2009 Westwood Professional Services, Inc. excavated the corner location with a Benton County backhoe. An 8-foot by 10-foot by 5-foot deep hole was excavated to original soil. At the surface a PK Nail was found. A 6-inch by 6-inch by 18-inch granite monument with center hole was found 3 feet below the surface.

A 365922

Benton County Surveyor's Office  
Jerome C. Wittstock, County Surveyor  
Minnesota License No. 19552

Additional excavation revealed no additional evidence of the corner position. The granite was found 2 feet east of the PK Nail. The found monument measures 2626.78 and 2626.50 feet to the northeast corner and southeast corners respectively and falls within a half a foot of being on a straight line between said corners. This fits the 1937 distances by about a foot. (Lunser's position to the north was not to the found granite at the northeast corner) Believing the granite monument to be the best available obliterated evidence, a 1/2-inch by 14-inch iron pipe capped 19552 was set to mark the corner position.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-156341.224  
E-526707.439