

Certified, Filed and or Recorded on
Nov. 06, 2008 AT 08:40AM


Signed: CK
MARILYN J NOVAK G V
BENTON COUNTY MINNESOTA
MARILYN J NOVAK
COUNTY RECORDER

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 16, Township 31N, Range 29W
4TH Principal Meridian, State of Minnesota, County of Benton

At the corner location shown on the sketch:

- On 23 OCT 2008 found a CAST IRON MONUMENT
- left monument as found lowered monument removed monument (explain)
- On _____ placed on _____



Statement of evidence for this corner location is on back of this page.

I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Land Surveyor under the laws of the State of Minnesota.

Signature Jan W. Oley
Deputy Benton County Surveyor
License No. 45872

Date: 11/04/2008

Benton County Surveyor's Office
 Jason W. Oberg, Deputy County Surveyor
 Minnesota License No. 45872

Statement of Evidence:

H163

East Quarter Corner of Section 16, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

12" Bur Oak	S 2 ½ E	16 links
12" Blk Ash	N 40 W	35 links

1937 County Engineer's Notebook No. 99 contains a road survey for CAR No. 28 running south to north. Notes show corner marked by a spike with fence line west. Ties:

FP.	NE	26.65'
FP.	E	28.3'

Stationing gives distances of 2719.4 feet to the SE corner and 2728.9 feet to the NE corner with a delta angle of 0-34' right.

1981 Paul Wellen, LS 10461, found a ¾" I.P. in the centerline of roads north/south and a fence line west. He replaced it with a cast iron monument. He filed a Certificate of Location (#160214). Notes give distances of 2730.93 feet to the NE corner and 2720.63 feet to the SE corner of Section 16.


2008 The County Surveyor's Office searched and found a cast iron monument at the centerline of north-south gravel road (105th Avenue N.E.). The position gives distances to the NE corner and SE corner as 2730.96 feet and 2720.64 feet respectively, which agree with reported 1937 distances of 2728.9 feet and 2719.4 feet, respectively, and subsequent 1981 survey by Wellen. The deflection from south to north measures at 0°32'33" right, which agrees with the deflection reported in 1937 (0-34' right). The Surveyor accepts the position as best evidence and updated ties.

County Coordinates to CIM by GPS
 NAD 83 (1996 Adjustment)
 N-150984.188
 E-526646.872

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

I hereby certify that on the 6th day of April, 19 81
 I did _____ find _____ the east quarter corner of Section 16,
 Twp. 37N, Rg. 29W, _____ Benton _____ County, Minnesota, which
 was evidenced by 3/4 inch iron pipe in the center line of a north-south
road opposite a fence line west.

I further certify that in order to perpetuate said corner I did
 at the exact location thereof place a permanent marker consisting
 of a Benton County Cast Iron Monument. and that
 I did establish witness or reference monuments as shown below:



160214 81-31 B-19 P-128

I hereby certify that the above
 is true and correct and that I am
 a registered Land Surveyor under
 the laws of the State of Minnesota.

Dan J. Allen

Minn. Registration No. 10461

Office of the County Recorder,
Benton County, Minn.

I hereby certify that the within instrument
 was filed for record in this office on the
10th day of September, 1981 at 2 P.M.

F.A. Johnson
 County Recorder

By _____ Deputy.