

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


North Quarter Corner of Section 11, Township 37, Range 29, 4th P.M.

STATE OF MINNESOTA, County of Benton

At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 9-04-92 placed a Cast Iron Monument (Down 0.3')
DATE

SKETCH OF REFERENCE TIES



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature] 2-16-93
SIGNATURE DATE

Registration No. 10461

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M. on the _____ day of _____ A.D., 19 _____

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence:

NORTH QUARTER CORNER, SECTION 11, T 37N, R 29W, 4TH P.M.

1. During the G.L.O. survey of 1855, Mr. Oscar F. Davis, a U.S. Deputy Surveyor, set a wood post to mark said corner.
2. Benton County's old surveyor's books provided no information to locate said corner.
3. On September 4, 1992, Paul E. Wellen & Associates searched for said corner at intersection of North-South tree line and center line of road. We accepted this North-South tree line as evidence of said corner. On September 4, 1992, we set a Cast Iron Monument at North-South tree line occupation and established new reference ties as indicated.

216305

OFFICE OF
BENTON COUNTY RECORDER
BENTON COUNTY, MN
CERTIFIED TO BE FILED
AND/OR RECORDED IN

JUL 14 1 24 PM '93

ALICE G. ENGELMEYER
COUNTY RECORDER

BY *[Signature]* DEPUTY