

Statement of Evidence:**J331**

North Quarter Corner of Section 33, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Bur Oak	S 73 W	235 links
8" W Oak	N 29 W	281 links

1920 County ties:

10" Bur Oak	SW	155.10
8" W. Oak	NW	185.46

1929 County Surveyor's Record Book 1, page 63 and Record Book A, Map No. 49 show a survey of Section 28 by M. B. Lang. Corner is shown marked by a stake with a distance of 2654 feet north to the center of Section 28.

1933 County Engineer's notebook No. 70 shows road survey by H. G. Elletson. Corner is shown in line with fences running north and south. Stationing gives distances of 2627.3 feet to the NW corner and 2629.2 feet to the NE corner.

2005 Sam DeLeo, LS 40341, excavated a hole that measured 6' by 6' to a depth of 3' at the lost position, (midway and on a straight line between section corners). This position fit well with the centerline of the E-W road and the fence line north. No evidence of a monument that marked the corner was found. Evidence of the accessories recorded in 1855 and 1920 were not found. A standard cast iron monument was set at the lost position which measured 2630.14 feet on a straight line from the NE and NW corners of the section. The 1929 dimension to the center section of Section 28 was not verified at this time.

County Coordinates to set corner:

NAD 83 (1996 Adjustment)

N- 105661.293

E- 555938.733