

Statement of Evidence: The North Quarter Corner of Section 12, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this Corner and a wood post was set for the Corner and bearing trees were recorded.

10" Aspen	N 60 E	30 links
6" Bur Oak	S 9 E	21 links

2002 Research of County records found no information on this Corner.

2004-2005 On 10/6/2005 The Minnesota Department of Transportation searched at a computed lost position. This location is approximately 45 feet south of an east - west fence line. Also an area at the lost distance along the fence was searched. There is an existing north-south fence north of the locations. An area of projected fence intersections was searched also. Nothing was found. In conjunction with the Benton County Surveyor, Gary H. Stevenson L.S. 12684, and Kyle Klasen MN/DOT LSIT, it was determined to locate the Corner at the intersection of the east-west fence and the north - south fence projected south. A MN/DOT cast iron monument was placed, with the top down 0.4 feet. New reference ties were made.

County Coordinates obtained by GPS (for reference only)
NAD 83 (1996 Adjustment) N-126695.38, E-507936.37

2010 On 1/20/2010, The Minnesota Department of Transportation again found a cast iron monument and reference ties. The Minnesota Department of Transportation accepts the cast iron monument as the correct location of the North Quarter Corner of Section 12, Township 36 North, Range 30 West, 4th Principal Meridian, Benton County, Minnesota.

For details and survey analysis, contact the Minnesota Department of Transportation District Surveys Office in Baxter, Minnesota.