

MARILYN J. NOVAK
COUNTY RECORDER
BY Marilyn J. Novak DEPUTY

OFFICE OF
BENTON COUNTY RECORDER
BENTON COUNTY, MN
CERTIFIED TO BE FILED
AND/OR RECORDED ON

291182

2002 OCT 30 P 3: 22

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 14, Township 36, Range 29
4TH Principal Meridian, State of Minnesota, County of BENTON


At the corner location shown on the sketch:

On _____ found a _____
DATE

left monument as found lowered monument removed monument (explain)

On 10/10/02 placed a CAST IRON MONUMENT
DATE

CO. RD. NO. 64



SPIKE - DISC
S. FACE
24" RED OAK
45.24'



SPIKE - DISC
N. FACE
26" BUR OAK
97.41'

Statement of evidence for this corner location is on back of this page.

I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Land Surveyor under the laws of the State of Minnesota.

Signature *Angela A. Steen* Date 10/14/02 License No. 12684

Title: Land Surveyor Professional Engineer County Surveyor County Engineer

Statement of Evidence:

K143

The East Quarter Corner of Section 14, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

In 1855, Oscar F. Davis set a wood post at this location and bearing trees were recorded.

12" Black Ash	N 38 1/2 E	46 links
6" Lynn	S 82 3/4 W	45 links

On December 22, 1914, the County Surveyors records for a road survey note that an old stake and one B.T. were found and a new W. Oak stake was set by J.P. Soderstrum. He also established the following reference ties.

12" Elm	E	51.8
8" W. Oak	SW	77.3

On May 13, 2002 Westwood Professional Services, Inc. searched for the corner and dug a hole with a backhoe, at the centerline of 125th Avenue NE (running north and south), 12' X 12' down to natural ground. We were looking for the white oak stake set in 1914. We did not find the stake but found two-10" lath stuck together (likely set by the Benton County Highway Department) and many large field stones. No positive evidence of the 1914 tie trees was found. The distance of 51.8 feet east did fall in a depression of a possible old stump, but no real evidence of an Elm was found. We established the corner using obliterated methods at the centerline of County Road 64 (running north and south) and a fence line to the east and evidence of former fence to the west. Landowner to the south states that a large red piece of metal was placed on the west side of the road at the location of the fence line to the west and two fence posts left along the 1/4 line.

On May 20, 2002 Westwood Professional Services, Inc. set a spike at the corner location as established above and on 10/10/02 the spike was replaced with a cast iron monument.

Reference Job #20025051

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-119449.66
E-537525.06